

DATA SHEET

Fiberglass rod Ø 4,5 mm including vertical steel cage

Profi-Set

inclusive accessories



INCL. ACCESSORIES



Standard-Set

without accessories



BEGINNING



RUNPOGLIDER with swivel and patented pressed flexible head with a bigger eyelet on top Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread, screwed to strand



Achtung!
Stromleitend
Achtung!
electric
conductive

ENDING



Ending joint with RUNPOTEC RTG Ø 6 mm thread






SPECIFICATION

(RRP/excl. of VAT)

LENGTH	30 m	40 m	50 m	60 m	80 m
WEIGHT (PROFI-SET)	4,365 kg	4,585 kg	4,805 kg	5,025 kg	5,480 kg
WEIGHT (STANDARD-SET)	3,489 kg	3,709 kg	3,929 kg	4,149 kg	4,589 kg
ITEM NO. (PROFI-SET)	10052	10055	10057	10047	10050
ITEM NO. (STANDARD-SET)	10054	10056	10058	10048	10051
PRICE € (PROFI-SET)	€ 212,50	€ 235,50	€ 256,50	€ 278,00	€ 322,50
PRICE € (STANDARD-SET)	€ 155,50	€ 178,50	€ 199,50	€ 221,00	€ 264,50
ROD MATERIAL	fiberglass core with PP sheath				

Recommended tube diameter, bending radius and tension loads of fiberglass rod Ø 4,5 mm

Ø			
4,5 mm	30–80 mm	120 mm	1300 Kg

DESCRIPTION / PROFI SET

Profi set fiberglass rod Ø 4,5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel cage (galvanized/powder coated) with new, double outlet system (automatic run-out brake and quick outlet), additional locking brake, extractable standing feet and stowage compartment for accessories. **Included accessories:** 1 x RUNPOGLEITER Ø 7 mm, 1 x starting spinner with shackle, 1 x roller aluminum/stainless steel, 1 x special glue (3 g), 1 x coupling joint (stainless steel), 2 x ending joint (stainless steel). Fiberglass rod tensile load 1300 kg, total tension load 220 kg.

DESCRIPTION / STANDARD SET

Standard set fiberglass rod Ø 4,5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel cage (galvanized/powder coated) with new, double outlet system (automatic run-out brake and quick outlet), additional locking brake. Fiberglass rod tensile load 1300 kg, total tension load 220 kg.