

DATA SHEET

Fiberglass rod Ø 6 mm including vertical steel cage

Profi-Set

inclusive accessories



INKL. ACCESSORIES



Standard-Set

without accessories



BEGINNING



RUNPOGLIDER with swivel and patented pressed flexible head with a bigger eyelet on top Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread, screwed to strand



ENDING



Ending joint with RUNPOTEC RTG Ø 6 mm thread






SPECIFICATION

(RRP/excl. of VAT)

LENGTH	40 m	50 m	60 m	80 m
WEIGHT (PROFI-SET)	7,820 kg	8,020 kg	8,220 kg	8,620 kg
WEIGHT (STANDARD-SET)	6,909 kg	7,109 kg	7,309 kg	7,709 kg
ITEM NO. (PROFI-SET)	10059	10061	10063	10065
ITEM NO. (STANDARD-SET)	10060	10062	10064	10066
PRICE € (PROFI-SET)	€ 263,00	€ 285,00	€ 311,00	€ 365,50
PRICE € (STANDARD-SET)	€ 216,00	€ 238,00	€ 264,00	€ 318,50
ROD MATERIAL	fiberglass core with PP sheath			

Recommended tube diameter, bending radius and tension loads of fiberglass rod Ø 6 mm

Ø			
6 mm	40–100 mm	168 mm	2200 Kg

DESCRIPTION / PROFI SET

Profi set fiberglass rod Ø 6 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel cage (galvanized/powder coated) with new, double outlet system (automatic run-out brake and quick outlet), additional locking brake, extractable standing feet and stowage compartment for accessories. **Included accessories:** 1 x RUNPOGLEITER Ø 7 mm, 1 x starting spinner with shackle, 1 x roller aluminum/stainless steel, 1 x special glue (3 g), 1 x coupling joint (stainless steel), 2 x ending joint (stainless steel). Fiberglass rod tensile load 2200 kg, total tension load 320 kg.

DESCRIPTION / STANDARD SET

Standard set fiberglass rod Ø 6 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel cage (galvanized/powder coated) with new, double outlet system (automatic run-out brake and quick outlet), additional locking brake. Fiberglass rod tensile load 2200 kg, total tension load 320 kg.